



Stock Heads

Brighton Tru-Edge Heads stocks stainless steel heads in both **ASME 2:1 Elliptical** and **ASME Flanged & Dished** styles. Stock heads are offered in **SA240 304/304L** dual certified and **SA240 316/316L** dual certified, and are formed without a center hole. Immediate shipment can be made on these stock heads, and Material Test Reports accompany every shipment.

2:1 Elliptical

Outside Diameter	Thickness	Straight Flange	Overall Height	Weight (lb.)
*6.625"	3/16"	1-3/4"	3-1/2"	6
	5/16"	1-3/4"	3-9/16"	9
*8.625"	3/16"	1-11/16"	3-15/16"	9
	5/16"	1-11/16"	4"	14
*10.75"	3/16"	2-1/8"	4-7/8"	14
	3/8"	2-1/8"	5"	25
*12.75"	3/16"	2-5/8"	5-7/8"	20
	3/8"	2-5/8"	6"	38
14"	3/16"	2-13/16"	6-3/8"	23
	3/8"	2-13/16"	6-1/2"	44
16"	3/16"	2-13/16"	6-7/8"	29
	3/8"	2-13/16"	7"	54
18"	3/16"	2"	6-5/8"	30
	1/4"	2"	6-5/8"	38
	3/8"	2"	6-11/16"	56
20"	3/16"	2"	7-1/8"	35
	3/8"	2"	7-3/16"	68
24"	3/16"	2"	8-1/8"	49
	1/4"	2"	8-1/8"	63
	3/8"	2"	8-3/16"	89
30"	1/4"	2"	9-5/8"	94
	3/8"	2"	9-11/16"	137
36"	1/4"	2"	11-1/8"	130
	3/8"	2"	11-3/16"	190
	1/2"	2"	11-1/4"	230
72"	3/8"	2"	20-3/16"	668
	1/2"	2"	20-1/4"	867




Provided with a 37-1/2 degree outside bevel and a 1/16" land.

* Meets A-403 Weld Cap Spec

ASME F&D

Outside Diameter	Thickness	Straight Flange	Overall Height	Weight (lb.)
12"	3/16"	1-1/2"	3.64"	13
	1/4"	1-1/2"	3.67"	16
14"	3/16"	1-1/2"	3.98"	16
	1/4"	1-1/2"	4"	21
16"	3/16"	1-1/2"	4.32"	20
	1/4"	1-1/2"	4.57"	26
18"	3/16"	1-1/2"	4.66"	25
	1/4"	1-1/2"	4.70"	32
20"	3/16"	1-1/2"	5"	30
	1/4"	1-1/2"	5.04"	39
24"	3/16"	1-1/2"	5.70"	41
	1/4"	1-1/2"	5.72"	53
30"	3/16"	1-1/2"	6.94"	66
	1/4"	1-1/2"	7"	81
36"	3/16"	1-1/2"	7.74"	85
	1/4"	1-1/2"	7.77"	110

Provided with a machined square edge.

-  Solution anneal and beveled at 37.5°, no land.
-  Solution anneal and beveled at 37.5°, no land.
-  Solution anneal and beveled at 37.5°, no land.