



## Carbon Steel Stock Heads

Outside Diameter	Thickness	Min	Bevel	LCVN	UT
24"	1"	.938"	37.5 deg OSB w/ 1/16" L	-	-
	3"	2.563"	30 deg OSB; No L	18/12, -50F	SA578 LVL C 100%
30"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.460"	37.5 deg OSB w/ 1/16" L	-	-
	0.750"	0.700"	37.5 deg OSB w/ 1/16" L	-	-
	1.250"	1.178"	30 deg OSB w/ 1/16" L	-	-
36"	0.375"	0.334"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
	0.625"	0.587"	37.5 deg OSB w/ 1/16" L	-	-
	1.375"	1.313"	30 deg OSB w/ 1/16" L	-	-
	1.5"	1.375"	30 deg OSB w/ 1/16" L	-	-
42"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
	1.625"	1.500"	30 deg OSB; No L	-	-
48"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.465"	37.5 deg OSB w/ 1/16" L	-	-
	0.625"	0.588"	37.5 deg OSB w/ 1/16" L	-	-
	1"	0.950"	37.5 deg OSB w/ 1/16" L	-	-
	1.75"	1.625"	30 deg OSB w/ 1/16" L	15/12, -50F	SA578 LVL C 100%
	2"	1.875"	30 deg OSB w/ 1/16" L	-	-
	2"	1.875"	30 deg OSB w/ 1/16" L	15/12, -50F	SA578 LVL C 100%
54"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
60"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
	0.625"	0.563"	37.5 deg OSB w/ 1/16" L	-	-
72"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
	0.625"	0.563"	37.5 deg OSB w/ 1/16" L	-	-
	0.750"	0.701"	37.5 deg OSB w/ 1/16" L	-	-
	1"	0.938"	30 deg OSB; No L	-	-
84"	0.625"	0.563"	37.5 deg OSB w/ 1/16" L	-	-
	0.750"	0.688"	37.5 deg OSB w/ 1/16" L	-	-
96"	0.375"	0.313"	37.5 deg OSB w/ 1/16" L	-	-
	0.500"	0.438"	37.5 deg OSB w/ 1/16" L	-	-
	0.625"	0.563"	37.5 deg OSB w/ 1/16" L	-	-
	0.750"	0.688"	37.5 deg OSB w/ 1/16" L	-	-